

APPENDIX B
VERSION WITH MARKINGS TO SHOW CHANGES MADE
37 C.F.R. § 1.121(b)(iii) AND (c)(ii)

CLAIMS:

1. A film scanner for converting [between] images on film [and] into electrical signals, comprising:

- a light source for scanning film;
- collection optics arranged to image light transmitted by the film through an imaged light path;
- one or more image light sensors arranged to receive the light from the collection optics through the imaged-light path and to produce one or more image signals representative of an image on the film;
- a reflector arrangement defining an internally reflective cavity and having at least one entrance aperture for receiving light transmitted by the film and one exit aperture for passing light to the one or more image light detectors and arranged to surround at least a portion of the imaged-light path;
- a scattered light sensor arranged in relation to the reflector arrangement to receive light which has been transmitted through the film but scattered by the film from the imaged-light path and reflected within the internally reflective cavity to produce a scattered light signal representative of the scattered light; and
- processing circuitry configured to receive the one or more image signals and the scattered light signal and having functionality to compensate the one or more image signals with reference to the scattered light signal.

3. A film scanner according to any one of [claim] claims 1 or 2, wherein the reflector arrangement includes a light collection lens system.

5. A film scanner according to claim 3 [or 4], wherein the light collection lens system comprises a second lens after the exit aperture.

6. A film scanner according to claim 3, [4 or 5,] further comprising a scanning lens for imaging the light source onto film, wherein the light collection lens system comprises a first lens

near the entrance aperture and wherein the exit aperture is circular and has a diameter substantially equal to the diameter of the image of the scanning lens formed by the first lens.

7. A film scanner according to [any preceding] claim 1, wherein the scattered light [detector] sensor is arranged to receive scattered light through a further exit aperture of the reflector arrangement.

9. A film scanner according to [any preceding] claim 1, wherein the processing circuitry includes a summing unit for summing a function of the scattered light signal with each of the one or more image signals.

10. A film scanner according to [any preceding] claim 1, wherein the one or more image signals are three image signals each representing respectively red, green and blue light, and wherein the collection optics are arranged to image light onto respective red, green and blue image light sensors via colour splitting optics.

12. A film scanner according to any one of [claim] claims 10 or 11, wherein the function is:

$$(\text{Scratch signal} \times k \times \text{colour}) / (a \times \text{red} + b \times \text{green} + c \times \text{blue})$$

where: "scratch signal" is the scattered light signal

"k" is a variable constant

"Colour" is the relevant colour image signal

"Red, green, blue" are the colour image signals

"a, b, c" are constants.

13. A film scanner according to any one of [claim] claims 9, 10, or [12] 11, wherein the processing circuitry includes a correction unit for correcting the scattered light signal for variations in the brightness of the light source.

16. A film scanner according to [any preceding] claim 1, wherein the [the] reflector arrangement is arranged between the film and subsequent light splitting and collection optics.

19. A light collection system according to any one of [claim] claims 17 or 18, wherein the reflector arrangement includes a light collection lens system.

21. A light collection system according to claim 19 [or 20], wherein the light collection lens system comprises a second lens after the exit aperture.

22. A light collection system according to claim [19, 20 or] 21, in which the film scanner has a scanning lens for imaging the light source onto film, wherein the light collection lens system comprises a first lens near the entrance aperture and wherein the exit aperture is circular and has a diameter of the image of the scanning lens formed by the first lens.

23. A light collection system according to any one of [claim] claims 17, 18, 19 or 20 [to 22], wherein the scattered light detector is arranged to receive scattered light through a further exit aperture of the reflector arrangement.

25. A light collection system according to any one of claims 17, 18, 19 or 20 [to 24], wherein the processing circuitry includes a summing unit for summing a function of the scattered light signal with each of the one or more image signals.

26. A light collection system according to any one of claims 17, 18, 19 or 20 [16 to 24], wherein the one or more image signals are three image signals each representing red, green and blue light, and wherein the collection optics are arranged to image light onto respective red, green and blue image light sensors via colour splitting optics.

29. A light collection system according to claim 26[, 27 or 28], wherein the processing circuitry includes a correction unit for correcting the scattered light signal for variations in the brightness of the light source.

32. A telecine comprising a film scanner according to any one of claims 1, 2, 7, 8, 9, 10, 11 or [to] 16.